

# edge Product Data Sheet

#### **Key Highlights:**

• Type: RJ45 SFP

• Compitability: Multi-Vendor MSA Compatible

• Media Type: Twisted Pair Cable

• Max. Distance: 100m

• Data Rate: 10/100/1000 Mbps

• Temperature: Industrial -45°- +85°C



### Optical Transceiver: 1000M-SFP-TI

### Product Description:

1000M-SFP-TI is Multi-Vendor MSA Compatible RJ45 SFP (Small Form-factor Pluggable) Transceiver, operating over twisted pair Category 5 or better cable with maximum distance up to 100m. 1000M-SFP-TI operates in Industrial -45° to 85°C temperature range and has RJ45 Standard connector. RJ45 SFP support 10-1000 Mbps data rates and such applications as 10Base-T, 100Base-T and 1000Base-T. 1000M-SFP-TI copper SFP transceiver is multi-purpose module used in number of different places of today's networking. Consequently, most popular applications are Enterprise networking for LAN applications and different other networking places still using copper connections.







## ge Product Data Sheet

RJ45 SFP Transceiver is CE/RoHS certified and it is Compliant with product safety standards. 1000M-SFP-TI Transceiver is fully compliant to SFP Multi Source Agreement INF-8074i. Consequently, it means that module is compatible with 80% of networking equipment, where is not implemented a special algorithm for protection against third party modules. However – our technical team has accumulated deep expertise in custom-encoded firmware's for RJ45 SFP transceiver in order to make it work in almost any brand equipment. We will be glad to know your requirements.

#### **Product Specification:**

General parameter	Value
Media Type:	Copper
Connectors:	RJ45
Maximum Distance:	100 m
Supported Data Rate:	10/100/1000 Mbps
Supported Applications:	1000Base-T, 100Base-T, 10Base-T
Operating Temperature Range:	Industrial -45° to 85°C
Storage Temperature Range:	- 45° to 85°C
Chipset:	MAXIM, MINDSPEED, SEMTECH, UX
Power Supply Voltage Typical:	+3.3V single power supply
Compliance:	CE, INF-8074i, RoHS, SFP MSA





# edge Product Data Sheet

#### Compatibility:

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more then 100 vendor brands in data and telecom communications industry:

MS - General MSA

AD - ADVA

**AE** - Advantech

AL - Alcatel (Nokia)

AT - Allied Telesis

AR - Arista

**AS** - Arris

**AV** - Avaya

**BC** - Barracuda

**BR** - Broadcom

**QL** - Cavium (Qlogic) **CR**- Ceragon

**CP** - Checkpoint

**CH** - Chelsio

**CN** - Ciena

CI - Cisco

LI - Cisco (Linksys)

**CE** - Comnet

**co** - Coriant

**DH** - Dahua

DC - DCN

**DL** - Dell & Force10

**DK** - D-Link

DZ - DZS(Dasan-Zhone)

EI - ECI

**EC** - EdgeCore

**EW** - EdgeWare

**EL** - Eltex

EM - EMC2

**EN** - Enterasys

**ER** - Ericsson

**EF** - EXFO

**EX** - Extreme Networks

F5 - F5 Networks

FI - Finisar

**FO** - Fortinet

**FU** - Fujitsu

**H3** - H3C

**HI** - Hirschmann

**HU** - Huawei

IB - IBM

**IF** - Infinera

IN - Intel

JU - Juniper Networks

**KM** - KeyMile

**KY** - KyLand

**LN** - Lenovo

ML - Mellanox

ME - Meraki (Cisco)

MT - MikroTik

MO - Moxa

MR - MRV

NC - NEC

NG - Netgear

NK - Nokia

NT - Nortel

NS - NSN

**OR** - Oracle

PA - Palo Alto Network

**PL** - Planet

**QC** - QCT(Quanta)

QN - QNAP

RD - RAD

**RW** - RadWare

**RC** - Raisecom

**RK** - Ruckus

**RU** - Ruijie Networks

SG - Samsung

SV - Sandvine

SC - Silicom

SF - SolarFlare

SW - Sonicwall

**SM** - Supermicro

SY - Synology

**TC** - Telco Systems

TP - TP-LINK

TN - Trendnet

**UN** - Ubiquiti Networks

VX - VeEx

WG - WatchGuard

WS - Waystream

WT - Westermo

ZT - ZTE

ZX - Zyxel

**HP** - HP AG - Avago

OC - Oclaro

**EU** - Emulex

TM - Transmode

**AU** - HP Aruba

XX - Other

### Warranty:

EDGE Optic's provides a limited warranty for sixty (60) months from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship. Warranty does not cover damage caused by improper deployment, misuse and accidents.



